

SEWER JETTING HOSE

Thermoplastic Hose

Brand
TAIYO



Construction

- Inner tube: Thermoplastic Elastomer
- Reinforcement : Single or double braid of synthetic fibre.
- Cover : Polyurethane, orange colour. Special colours and private print upon request.

Application and Temperature Range

- Standard Sewer Cleaning vehicles and Sewer Cleaning equipment. Special fully bonded construction and optimum cut and wear resistance, for an increased lifetime. Cover resistant to microbiological degradation. Lightweight compared to conventional rubber sewer cleaning hoses. Available in customary length.
- Temperature standards: -40°C + 60°C

Size		I.D.		O.D.		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Dash	DN	inch	mm	inch	mm	PSI	in bar	PSI	in bar	mm	inch
3	5	3/16	4,8	0,40	10,3	2.500	175	6.250	438	40	1,6
4	6	1/4	6,4	0,49	12,4	2.500	175	6.250	438	40	1,6
8	12	1/2	12,7	0,81	20,6	2.500	175	6.250	438	100	4,0
12	20	3/4	19,1	1,15	29,2	2.500	175	6.250	438	125	5,0
16	25	1	25,4	1,45	36,8	2.500	175	6.250	438	160	6,4
20	32	1.1/4	32,0	1,80	45,7	2.500	175	6.250	438	250	10,0



FLEXITUBE ENGINEERING SDN. BHD. (1034024-V)
Tel: 603-6263 9303 / 603-6279 9303 | Fax: 603-6280 6303
Website: Flexitube.com.my | Email: enquiry@flexitube.com.my